

Declaration of Conformity (DoC)

We, Shenzhen DOKE Electronic Co., Ltd

801, Building3, 7th Industrial Zone, Yulv Community, Yutang Road, Guangming District,
Shenzhen, China.

Declare that the DoC is issued under our sole responsibility and belongs to the following product(s):

Product Type: Tablet PC
Trademark : Blackview
Model Number(s): Active 10 Pro

(Name of product, type or model, batch or serial number)

System components:

PIFA Antenna:BT/Wi-Fi2.4G:-0.6dBi; WIFI5G:-0.6dBi;
GSM900:1.65dBi/DCS1800:0.12dBi; WCDMA Band I: 4.88dBi,Band VIII:1.65dBi;
LTE: B1: 4.88 dBi; B3:0.12 dBi; B7:1.96 dBi; B8: 1.65 dBi;
B20: 2.08 dBi; B28:0.39 dBi; B40: 2.44 dBi;B41: 3.48 dBi;

Adapter:

Model: QZ-05500EC00

Input: 100-240V~50/60Hz 1.2A

Output: 5.0V $\overline{\text{---}}$ 2.0A

Output(PD): 5.0V $\overline{\text{---}}$ 3.0A

or 9-20V $\overline{\text{---}}$ 3-2.75A(MAX)

Manufacturer: Guangdong Quanzhi Technology Co., Ltd.

RechargeableLi-ionBattery:

Model:Li506482PLGY; Specification:DC 3.87V, 30000mAh,116.1Wh;

Manufacturer: Shenzhen Huatiantong Technology Co.,Ltd.



The object of the declaration described above is in conformity with the essential requirements of the relevant Union harmonization legislation: Radio Equipment Directive *RED (2014/53/EU)*.

The following *harmonized* standards and technical specifications have been applied:

HEALTH & SAFETY (Art. 3(1)(a)):

EN 50566:2017;

EN 62209-2:2010;

EN 62479:2010;

EN IEC 62368-1:2020+A11:2020

EMC (Art. 3(1)(b)):

ETSI EN 301 489-1 V2.2.3 (2019-11)

ETSI EN 301 489-3 V2.3.2 (2023-01)

ETSI EN 301 489-17 V3.2.4 (2020-09)

ETSI EN 301 489-19 V2.2.1 (2022-09)

ETSI EN 301 489-52 V1.2.1 (2021-

11) EN 55032:2015+A1:2020

EN 55035:2017+A11:2020

EN IEC 61000-3-2:2019+A1:2021

EN 61000-3-3:2013+A2:2021

Radio Spectrum (Article 3.2):

EN 301 511 V12.5.1 (2017-03);

EN 301 908-1 V15.1.1 (2021-09);

EN 301 908-2 V13.1.1 (2020-06);

EN 301 908-13 V13.2.1 (2022-02);

ETSI TS 138 521-1 (V16.4.0) (2020-09)

ETSI TS 138 521-3 (V16.4.0) (2020-09)

EN 300 328 V2.2.2 (2019-07);
EN 301 893 V2.1.1 (2017-05);
EN 300 330 V2.1.1 (2017-02)
EN 300 440 V2.2.1 (2018-07);
EN 303 413 V1.2.1 (2021-04);
EN 303 345-1 V1.1.1 (2019-06);
EN 303 345-3 V1.1.1 (2021-06);

Notified Body Involved:

Notified Body Name: Eurofins Electrical and Electronic Testing NA,
Inc. Notified Body Number: 0980
Notified Body Assessment Performed: Module B/C on Article 3.1a, 3.1b, 3.2
EU-type examination certificate number: 3552-11-2024-240802

RF Specification:

Function	Operaton Frequency	Max RF output power:
BLE	2402MHz~2480MHz	5.64dBm
BT(BR+EDR)	2402MHz~2480MHz	4.65dBm
WIFI 802.11b/g/n(HT20/40)	802.11b/g/n(20MHz): 2412~2472MHz; 802.11n(40MHz):2422~2462MHz	16.74dBm
Wi-Fi 5.2G(802.11a/n20/n40/ac20/ac40/ac80)	802.11a/ n20/ac20:5180MHz~5240MHz 802.11 n40/ac40:5190MHz~5230MHz 802.11 ac80:5210MHz	14.88dBm
Wi-Fi 5.8G(802.11a/n20/n40/ac20/ac40/ac80)	802.11a/ n20/ac20:5745MHz~5825MHz 802.11 n40/ac40:5755MHz~5795MHz 802.11ac80:5775MHz	12.57dBm
GSM/GPRS/EGPRS 900	TX(Uplink):880M-915MHZ; RX(Downlink):925M-960MHZ	32.97 dBm
GSM/GPRS/EGPRS 1800	TX(Uplink):1710M-1785MHZ; RX(Downlink):1805M-1880MHZ	30.37 dBm
WCDMA B1	TX(Uplink):1920-1980MHz; RX(Downlink):2110-2170MHz	23.09 dBm
WCDMA B8	TX(Uplink): 880-915MHz; RX(Downlink):925-960MHz	22.85 dBm
LTE FDD B1	TX(Uplink):1920-1980MHz; RX(Downlink):2110-2170MHz	23.11dBm
LTE FDD B3	TX(Uplink) :1710-1785MHz; RX(Downlink):1805-1880MHz	23.18 dBm
LTE FDD B7	TX(Uplink) :2500-2570MHz; RX(Downlink):2620-2690MHz	23.95 dBm
LTE FDD B8	TX(Uplink): 880MHz to 915 MHz RX(Downlink): 925 MHz to 960 MHz	23.35 dBm
LTE FDD B20	TX(Uplink): 832MHz~862MHz; RX(Downlink):791MHz~821MHz	23.35 dBm
LTE FDD B28	TX(Uplink): 703 MHz to 748MHz RX(Downlink): 758 MHz to 803 MHz	23.69 dBm
LTE TDD B40	Uplink & Downlink: 2300 MHz to 2400 MHz	23.77 dBm
LTE TDD B41	Uplink & Downlink: 2496 MHz to 2690 MHz	24.67 dBm
NR FDD n1:	Uplink: 1920 MHz to 1980MHz Downlink: 2110 MHz to 2170 MHz	24.1 dBm
NR FDD n3:	Uplink: 1710 MHz to 1785 MHz Downlink: 1805 MHz to 1880 MHz	24.39 dBm
NR FDD n8:	Uplink: 880 MHz to 915 MHz Downlink: 925 MHz to 960 MHz	23.53 dBm
NR FDD n20:	Uplink: 832 MHz to 862 MHz Downlink: 791 MHz to 821 MHz	23.77 dBm
NR FDD n28:	Uplink: 703 MHz to 748 MHz	25.68 dBm

	Downlink: 758 MHz to 803 MHz	
NR TDD n40:	Uplink & Downlink: 2300 MHz to 2400 MHz	24.05 dBm
NR TDD n41:	Uplink & Downlink: 2496 MHz to 2690 MHz	26.18 dBm
NR TDD n77:	Uplink & Downlink: 3300 MHz to 4200 MHz	27.16 dBm
NR TDD n78	Uplink & Downlink: 3300 MHz to 3800 MHz	27.07 dBm
NFC	13.56MHz	-8.69 dBuA/m@10m
FM	Rx(Downlink): 87.5MHz~108MHz	--
GPS	Rx(Downlink): 1.57542GHz	--

Tests for SAR are conducted using standard operating positions with the device transmitting at its highest certified power level in all tested frequency bands. The maximum SAR values tested on this device when used in its normal position at the ear and when used close to the body (at a minimum distance of 5mm/0mm) are:

Max SAR Value(W/kg) Limit is 2.0(W/kg) for 10-g	10-g Body	1.339W/kg
Limit is 4.0(W/kg) for 10-g	10-g Member DAS	2.943W/kg

Technical file held by: Shenzhen DOKE Electronic Co., Ltd
801, Building3, 7th Industrial Zone, Yulv Community, Yutang Road, Guangming District, Shenzhen, China.

Signed for and on behalf of:
Name and Title:
Address:

Shenzhen DOKE Electronic Co., Ltd
zhang.liuwei /Manager
801, Building3, 7th Industrial Zone, Yulv Community,
Yutang Road, Guangming District, Shenzhen, China.

zhang.liuwei

Signature of Authorized Person
2024-11-11