

Declaration of Conformity (DoC)

We, **Shenzhen DOKE Electronic Co., Ltd.**

801, Building3, 7th Industrial Zone, Yulv Community, Yutang Road, Guangming District, Shenzhen, China.

Declare that the DoC is issued under our sole responsibility and belongs to the following product(s):

Product Type: Smart phone
Trademark : Blackview
Model Number(s): BL9000, BL9000 Pro

(Name of product, type or model, batch or serial number)

System components:

PIFAAntenna:BT/Wi-Fi2.4G:1.1dBi; WIFI5G:1.1 dBi;

GSM900:0.6dBi/DCS1800:0.6dBi; WCDMABandI : 0.6dBi,BandVIII
:0.6dBi;

LTE:Band1: 0.5 dBi;Band3: 0.5dBi;Band7: 0.5 dBi;Band8: 0.5dBi;

Band20:0.5 dBi;Band28:0.5 dBi; Band34:0.5 dBi; Band38:0.5 dBi; Band408:0.5 dBi; Band41:0.5 dBi;

NR n1:0.5dBi; n3:0.5dBi; n7:0.5dBi; n8:0.5dBi; n20:0.5dBi; n28:0.5dBi; n38:0.5dBi; n40:0.5dBi; n41:0.5dBi;
n77:0.5dBi; n78:0.5dBi;

Adapter :

Model: QZ-12001EC00

Input: 100-240V~50/60Hz 3.0A Max

Output: 5.0V ---3.0A(15.0W)

or 9.0V ---3.0A(27.0W)

or 12.0V ---3.0A(36.0W)

or 15.0V ---3.0A(45.0W)

or 20.0V ---6.0A(120.0W)

(PPS)3.3V-20.0V ---6.0A (120.0W Max)

Manufacturer: Guangdong Quanzhi Technology Co., Ltd.

RechargeableLi-ionBattery:

Model:Li466383HTT; Specification:DC 7.82V, 4400mAh,34.408Wh;

Manufacturer: Shenzhen Huatiantong Technology Co.,Ltd.

USB Cable: 100cm;



The object of the declaration described above is in conformity with the essential requirements of the relevant Union harmonization legislation: Radio Equipment Directive RED (2014/53/EU).

The following *harmonized* standards and technical specifications have been applied:

HEALTH & SAFETY (Art. 3(1)(a)):

EN 50360:2017; EN 50566:2017; EN 62209-1:2016; EN 62209-2:2010;
EN 62479:2010
EN IEC 62368-1:2020+A11:2020

EMC (Art. 3(1)(b)):

ETSI EN 301 489-1 V2.2.3 (2019-11)
ETSI EN 301 489-3 V2.1.1 (2019-03)
ETSI EN 301 489-17 V3.2.4 (2020-09)
ETSI EN 301 489-19 V2.1.1 (2019-04)
ETSI EN 301 489-52 V1.2.1 (2021-
11) EN 55032:2015+A1:2020
EN 55035:2017+A11:2020
EN IEC 61000-3-2:2019+A1:2021
EN 61000-3-3:2013+A2:2021

Radio Spectrum (Article 3.2):

EN 301 511 V12.5.1 (2017-03);
EN 301 908-1 V15.1.1 (2021-09);
EN 301 908-2 V13.1.1 (2020-06);
EN 301 908-13 V13.2.1 (2022-02);
ETSI TS 138.521-1 (V16.4.0) (2020-09)
ETSI TS 138.521-3 (V16.4.0) (2020-09)
EN 300 328 V2.2.2 (2019-07);
EN 301 893 V2.1.1 (2017-05);
EN 300 440 V2.2.1 (2018-07);
EN 303 413 V1.2.1 (2021-04);
EN 303 345-1 V1.1.1 (2019-06);
EN 303 345-3 V1.1.1 (2021-06);
EN 300 330 V2.1.1 (2017-02)

Notified Body Involved:

3.3(g) Emergency Services: DELEGATED REGULATION (EU) 2019/320

Notified Body Name: Eurofins Electrical and Electronic Testing NA,
Inc. Notified Body Number: 0980

Notified Body Assessment Performed: Module B/C on Article 3.1a, 3.1b, 3.2

EU-type examination certificate number: 2733-12-2023-230479

RF Specification:

Function	Operation Frequency	Max RF outputpower:
BLE	2402MHz–2480MHz	5.01dBm
BT(BR+EDR)	2402MHz–2480MHz	8.46dBm
WIFI 802.11b/g/ n(HT20/40)	802.11b/g/n(20MHz): 2412~2472MHz; 802.11n(40MHz):2422~2462MHz	16.32dBm
Wi-Fi 5.2G(802.11a/n20/n 4	802.11a/ n20/ac20:5180MHz~5240MHz 802.11 n40/ac40:5190MHz~5230MHz 802.11 ac80:5210MHz	17.69dBm
Wi-Fi 5.8G(802.11a/n20/n 4	802.11a/ n20/ac20:5745MHz~5825MHz 802.11 n40/ac40:5755MHz~5795MHz 802.11ac80:5775MHz	13.6dBm
GSM/GPRS/EGPRS 900	TX(Uplink):880M-915MHZ; RX(Downlink):925M-960MHZ	33.73dBm
GSM/GPRS/EGPRS 1800	TX(Uplink):1710M-1785MHZ; RX(Downlink):1805M-1880MHZ	31.48dBm
WCDMA B1	TX(Uplink):1920-1980MHz; RX(Downlink):2110-2170MHz	25.65dBm
WCDMA B8	TX(Uplink): 880-915MHz; RX(Downlink):925-960MHz	24.17dBm
LTE FDD B1	TX(Uplink):1920-1980MHz; RX(Downlink):2110-2170MHz	24.78dBm
LTE FDD B3	TX(Uplink) :1710-1785MHz; RX(Downlink):1805-1880MHz	23.89dBm
LTE FDD B7	TX(Uplink) :2500-2570MHz; RX(Downlink):2620-2690MHz	24.3dBm
LTE FDD B8	TX(Uplink): 880MHz to 915 MHz RX(Downlink): 925 MHz to 960 MHz	23.36 dBm
LTE FDD B20	TX(Uplink): 832MHz~862MHz; RX(Downlink): 791MHz~821MHz	23.42dBm
LTE FDD B28	TX(Uplink):703 MHz to 748MHz RX(Downlink): 758 MHz to 803 MHz	23.45dBm
LTE TDD 34	TX(Uplink)& RX(Downlink) 2010 MHz to 2025 MHz	24.12 dBm
LTE TDD 38	TX(Uplink)& RX(Downlink) 2570 MHz to 2620 MHz	24.4 dBm
LTE TDD B40	TX(Uplink)& RX(Downlink) 2300 MHz to 2400 MHz	22.49dBm
LTE TDD B41	TX(Uplink)& RX(Downlink) 2496 MHz to 2400 MHz	24.8dBm
NR FDD n1	TX(Uplink): 1920 MHz to 1980MHz; RX(Downlink): 2110 MHz to 2170 MHz	23.39dBm
NR FDD n3	TX(Uplink): 1710 MHz to 1785 MHz;	23.41dBm

	RX(Downlink): 1805 MHz to 1880 MHz	
NR FDD n7	TX(Uplink): 2500 MHz to 2570 MHz; RX(Downlink): 2620 MHz to 2690 MHz	23.83 dBm
NR FDD n8	TX(Uplink): 880 MHz to 815 MHz; RX(Downlink): 925 MHz to 960 MHz	24.4dBm
NR FDD n20	TX(Uplink): 832 MHz to 862 MHz; RX(Downlink): 791 MHz to 821 MHz	24.01dBm
NR FDD n28	TX(Uplink): 703 MHz to 748 MHz; RX(Downlink): 758 MHz to 803 MHz	24.19dBm
NR TDD n38	Uplink & Downlink: 2570 MHz –2620 MHz	25.11 dBm
NR TDD n40	Uplink & Downlink: 2300 MHz to 2400 MHz	21.69 dBm
NR TDD n41	Uplink & Downlink: 2496MHz-2690MHz	21.13 dBm
NR TDD B77	Uplink & Downlink: 3300 MHz to 4200 MHz	21.84 dBm
NR TDD B78	Uplink & Downlink: 3300 MHz – 3800 MHz	21.15 dBm
NFC	13.56 MHz	3.34dBuA/m@10m
FM	Rx(Downlink): 87.5MHz~108MHz	--
GPS	Rx(Downlink): 1.57542GHz	--

Tests for SAR are conducted using standard operating positions with the device transmitting at its highest certified power level in all tested frequency bands. The maximum SAR values tested on this device when used in its normal position at the ear and when used close to the body (at a minimum distance of 5mm/0mm) are:

Max SAR Value(W/kg)	10-g Head	1.243W/kg
Limit is 2.0(W/kg) for 10-g	10-g Body	1.808W/kg
Limit is 4.0(W/kg) for 10-g	10-g Member DAS	3.985W/kg

Technical file held by:Shenzhen DOKE Electronic Co., Ltd

801, Building3, 7th Industrial Zone, Yulv Community, Yutang Road, Guangming District, Shenzhen, China.

Signed for and on behalf of: Shenzhen DOKE Electronic Co., Ltd

Name and Title: zhang.liuwei/Manager

Address: 801, Building3, 7th Industrial Zone, Yulv Community, Yutang Road, Guangming District, Shenzhen, China.

zhang.liuwei

Signature of Authorized Person

2023-12-19