

# Declaration of Conformity (DoC)

We, **Shenzhen DOKE Electronic Co.,Ltd.**

801, Building3, 7th Industrial Zone, Yulv Community, Yutang Road, Guangming District, Shenzhen, China.

**Declare that the DoC is issued under our sole responsibility and belongs to the following product(s):**

**Product Type:** Smart phone

**Trademark :** Blackview

**Model Number(s):** BV7300

(Name of product, type or model, batch or serial number)

System components:

PIFA Antenna: BT/Wi-Fi 2.4G: 2.74dBi; WIFI 5G: 4.42dBi;

GSM900: -0.41dBi/DCS1800: 0.76dBi; WCDMA Band I: 0.79dBi, Band VIII: -0.41dBi;

LTE: Band I: 0.79dBi; Band III: 0.85dBi; Band VII: 2.74dBi; Band VIII: -0.41dBi;

Band XX: -0.50dBi; B28: -1.66dBi; Band XL: 1.97dBi; Band XLI: 2.90dBi;

Adapter :

Model: QZ-04501EC00

Input: 100-240V~50/60Hz 1.2A

Output(PD): 5.0V ---3.0A 15.0W

or 9.0V ---3.0A 27.0W

or 12.0V ---2.5A 30.0W

or 15.0V ---2.0A 30.0W

or 20.0V ---2.25A 45.0W MAX

(PPS) 5.0V-11.0V ---3.0A 33.0W MAX

(PPS) 5.0V-20.0V ---2.25A 45.0W MAX

Manufacturer: Guangdong Quanzhi Technology Co., Ltd.

Rechargeable Li-ion Battery:

Model: LiH676590HT; Specification: DC 3.85V, 15000mAh, 57.75Wh;

Manufacturer: Shenzhen Huatiantong Technology Co., Ltd.

USB Cable: 100cm



**The object of the declaration described above is in conformity with the essential requirements of the relevant Union harmonization legislation: Radio Equipment Directive *RED (2014/53/EU)*.**

**The following *harmonized* standards and technical specifications have been applied:**

**HEALTH & SAFETY (Art. 3(1)(a)):**

EN 50360:2017;  
EN 50566:2017;  
EN 62209-1:2016;  
EN 62209-2:2010;  
EN 62479:2010  
EN IEC 62368-1:2020+A11:2020

**EMC (Art. 3(1)(b)):**

ETSI EN 301 489-1 V2.2.3 (2019-11)  
ETSI EN 301 489-3 V2.3.2 (2023-01)  
ETSI EN 301 489-17 V3.2.4 (2020-09)  
ETSI EN 301 489-19 V2.2.1 (2022-09)  
ETSI EN 301 489-52 V1.2.1 (2021-11)  
EN 55032:2015+A1:2020  
EN 55035:2017+A11:2020  
EN IEC 61000-3-2:2019+A1:2021  
EN 61000-3-3:2013+A2:2021

**Radio Spectrum (Article 3.2):**

EN 301 511 V12.5.1 (2017-03);  
EN 301 908-1 V15.2.1 (2023-01);  
EN 301 908-2 V13.1.1 (2020-06);  
EN 301 908-13 V13.2.1 (2022-02);  
EN 300 328 V2.2.2 (2019-07);  
EN 301 893 V2.1.1 (2017-05);  
EN 300 330 V2.1.1 (2017-02)  
EN 300 440 V2.2.1 (2018-07);  
EN 303 413 V1.2.1 (2021-04);  
EN 303 345-1 V1.1.1 (2019-06);  
EN 303 345-3 V1.1.1 (2021-06);

**Notified Body Involved:**

Notified Body Name: Eurofins Electrical and Electronic Testing NA,  
Inc. Notified Body Number: 0980

Notified Body Assessment Performed: Module B/C on Article 3.1a, 3.1b, 3.2

EU-type examination certificate number: 3482-10-2024-240732

## RF Specification:

| Function                      | Operation Frequency                                                                         | Max RF outputpower: |
|-------------------------------|---------------------------------------------------------------------------------------------|---------------------|
| BLE                           | 2402MHz~2480MHz                                                                             | -2.77 dBm           |
| BT(BR+EDR)                    | 2402MHz~2480MHz                                                                             | 7.71 dBm            |
| WIFI 802.11b/g/n(HT20/40)     | 802.11b/g/n(20MHz): 2412~2472MHz;<br>802.11n(40MHz):2422~2462MHz                            | 13.57 dBm           |
| Wi-Fi<br>5.2G(802.11a/n20/n4) | 802.11a/ n20/ac20:5180MHz~5240MHz<br>802.11 n40/ac40:5190MHz~5230MHz<br>802.11 ac80:5210MHz | 13.94 dBm           |
| Wi-Fi<br>5.8G(802.11a/n20/n4) | 802.11a/ n20/ac20:5745MHz~5825MHz<br>802.11 n40/ac40:5755MHz~5795MHz<br>802.11ac80:5775MHz  | 13.92 dBm           |
| GSM/GPRS/EGPRS<br>900         | TX(Uplink):880M-915MHZ;<br>RX(Downlink):925M-960MHZ                                         | 32.07 dBm           |
| GSM/GPRS/EGPRS<br>1800        | TX(Uplink):1710M-1785MHZ;<br>RX(Downlink):1805M-1880MHZ                                     | 29.71 dBm           |
| WCDMA B1                      | TX(Uplink):1920-1980MHz;<br>RX(Downlink):2110-2170MHz                                       | 23.26 dBm           |
| WCDMA B8                      | TX(Uplink): 880-915MHz;<br>RX(Downlink):925-960MHz                                          | 22.39 dBm           |
| LTE FDD B1                    | TX(Uplink):1920-1980MHz;<br>RX(Downlink):2110-2170MHz                                       | 22.62 dBm           |
| LTE FDD B3                    | TX(Uplink) :1710-1785MHz;<br>RX(Downlink):1805-1880MHz                                      | 24.11 dBm           |
| LTE FDD B7                    | TX(Uplink) :2500-2570MHz;<br>RX(Downlink):2620-2690MHz                                      | 23.53 dBm           |
| LTE FDD B8                    | TX(Uplink): 880MHz to 915 MHz<br>RX(Downlink): 925 MHz to 960 MHz                           | 22.98 dBm           |
| LTE FDD B20                   | TX(Uplink): 832MHz~862MHz;<br>RX(Downlink): 791MHz~821MHz                                   | 23.07 dBm           |
| LTE FDD B28a                  | TX(Uplink): 703 MHz to 733MHz<br>RX(Downlink): 758 MHz to 788 MHz                           | 24.29 dBm           |
| LTE FDD B28b                  | TX(Uplink): 718 MHz to 748MHz<br>RX(Downlink): 773 MHz to 803 MHz                           | 24.01 dBm           |
| LTE TDD B40                   | TX(Uplink)& RX(Downlink)<br>2300 MHz to 2400 MHz                                            | 23.90 dBm           |
| LTE TDD B41                   | TX(Uplink)& RX(Downlink)<br>2496 MHz to 2690 MHz                                            | 23.55 dBm           |
| NFC                           | 13.56MHz                                                                                    | 12.64 dBuA/m@10m    |
| FM                            | Rx: 87.5MHz~108MHz                                                                          | --                  |
| GPS                           | Rx: 1.57542GHz                                                                              | --                  |

Tests for SAR are conducted using standard operating positions with the device transmitting at its highest certified power level in all tested frequency bands. The maximum SAR values tested on this device when used in its normal position at the ear and when used close to the body (at a minimum distance of 5mm/0mm) are:

|                                                    |                 |           |
|----------------------------------------------------|-----------------|-----------|
| Max SAR Value(W/kg)<br>Limit is 2.0(W/kg) for 10-g | 10-g Head       | 0.246W/kg |
|                                                    | 10-g Body       | 1.042W/kg |
| Limit is 4.0(W/kg) for 10-g                        | 10-g Member DAS | 3.013W/kg |

Technical file held by:Shenzhen DOKE Electronic Co., Ltd  
801, Building3, 7th Industrial Zone, Yulv Community, Yutang Road, Guangming District, Shenzhen, China.

**Signed for and on behalf of:** Shenzhen DOKE Electronic Co., Ltd  
**Name and Title:** zhang.liuwei/Manager  
**Address:** 801, Building3, 7th Industrial Zone, Yulv Community, Yutang Road, Guangming District, Shenzhen, China.

zhang.liuwei  
Signature of Authorized Person  
2024-10-09