# Declaration of Conformity (DoC)

We, Shenzhen Doke Electronic Co., LTD
801, Building3, 7th Industrial Zone, Yulv Community, Yutang Road, Guangming District, Shenzhen, China

**Declare that the DoC is issued under our sole responsibility and belongs to the following product(s):**

| | |
|---|---|
| **Product Type:** | Smart Phone |
| **Trademark**: | Blackview |
| **Model Number(s):** | ROCK 2 |

(Name of product, type or model, batch or serial number)

System components:

PIFA Antenna: BT/Wi-Fi2.4G:1.5dBi; WIFI5G:1.9dBi

GSM 900:-1.6 dBi, GSM 1800:1.4 dBi
WCDMA B1 1.5 dBi, WCDMA B8 -1.7 dBi
LTE B1 1.5 dBi, LTE B3 1.4 dBi, LTE B7 1.3 dBi, LTE B8 -1.7 dBi, LTE B20 -1.3 dBi, LTE B28 -1.9 dBi
NR n1: 1.5 dBi, NR n3: 1.4 dBi, NR n8: -1.7 dBi, NR n20: -1.3 dBi, NR n28: -1.8 dBi, NR n40: 1.4 dBi,
NR n77: 2.1 dBi, NR n78: 2 dBi

GPS: PIFA Antenna

Adapter:

Model: HJ-C6-33-EU

Input: 100-240V~50/60Hz 0.8A

Output: 5.0V⎓3.0A 15.0W OR 9.0V⎓3.0A 27.0W OR 12.0V⎓2.5A 30.0W OR15.0V⎓2.0A 30.0W

OR 20.0V⎓1.5A 30.0W
PPS:3.3V-11V⎓3.0A 33.0W MAX

Manufacturer: SHEN ZHEN HUAJIN ELECTRONICS CO.. LTD

Rechargeable Li-ion Battery:

Model: LiU536587PHTT; Specification: DC 3.85V, 15000mAh

Manufacturer: SHENZHEN HUATIANTONG TECHNOLOGY CO.LTD

USB Cable: 100cm;



**The object of the declaration described above is in conformity with the essential requirements of the relevant Union harmonization legislation: Radio Equipment Directive *RED (2014/53/EU)*.**

**The following *harmonized* standards and technical specifications have been applied:**

**HEALTH & SAFETY (Art. 3(1)(a)):**

EN 50360:2017/A1:2023 EN 50566:2017/A1:2023 EN IEC/IEEE 62209-1528:2021 EN 50663:2017 EN 62479:2010

EN IEC 62368-1:2020+A11:2020

**EMC (Art. 3(1)(b)):**

ETSI EN 301 489-1 V2.2.3 (2019-11)

ETSI EN 301 489-3 V2.3.2 (2023-01)

ETSI EN 301 489-17 V3.3.1 (2024-09)

ETSI EN 301 489-19 V2.2.1 (2022-09)

ETSI EN 301 489-52 V1.3.1 (2024-11)

EN 55032:2015/A11:2020; EN 55035:2017/A11:2020

EN IEC 61000-3-2:2019/A2:2024; EN 61000-3-3:2013/A2:2021/AC:2022

**Radio Spectrum (Article 3.2):**

ETSI EN 301 511 V12.5.1 (2017-03);

ETSI EN 301 908-1 V15.2.1 (2023-01)

ETSI EN 301 908-25 V15.1.1 (2024-10)

ETSI EN 301 908-2 V13.1.1 (2020-06)

ETSI EN 301 908-13 V13.3.1 (2024-10)

EN 300 328 V2.2.2 (2019-07);

EN 301 893 V2.1.1 (2017-05);

EN 300 440 V2.2.1 (2018-07);

EN 303 413 V1.2.1 (2021-04);

EN300 330 V2.1.1 (2017-02)

The submitted samples of the above equipment has been tested and found to comply with the following European Directives:
**RoHS Directive 2011/65/EU & (EU) 2015/863**

**Notified Body Involved:**

Notified Body Name: DERYCOM CERTIFICATION SERVICES, INC.
Notified Body Number: 3052
Notified Body Assessment Performed: Module B/C on Article 3.1a, 3.1b, 3.2
EU-type examination certificate number: JEC-44

RF Specification:

| Functon | Operaton Frequency | Max RF output power: |
|---|---|---|
| BLE | 2402MHz–2480MHz | 2.17dBm |
| BT(BR+EDR) | 2402MHz–2480MHz | 3.09 dBm |
| WIFI 2.4G<br>802.11b/n(20MHz):<br>802.11n(40MHz): | 802.11b/n(20MHz):2412-2472MHz<br>802.11n(40MHz):2422~2462MHz | 14.07dBm |
| Wi-Fi 5.2G<br>802.11a/n/ac (20MHz):<br>802.11n/ac(40MHz): | 802.11a/n/ac<br>(20MHz):5180~5240MHZ<br>802.11n/ac(40MHz):5190~5230MHZ<br>802.11ac(80MHz):5210MHz | 13.17dBm |
| Wi-Fi 5.8G<br>802.11a/n/ac (20MHz):<br>802.11n/ac(40MHz):<br>802.11ac (80MHz): | 802.11a/n/ac(20MHz):5745~5825MHz<br>802.11n /ac(40MHz):5755~5795MHz<br>802.11ac (80MHz):5775MHz | 10.95 dBm |
| GSM/GPRS/EGPRS 900 | TX(Uplink):880M-915MHZ;<br>RX(Downlink):925M-960MHZ | 33.96dBm |
| GSM/GPRS/EGPRS 1800 | TX(Uplink):1710M-1785MHZ;<br>RX(Downlink):1805M-1880MHZ | 28.95dBm |
| WCDMA B1 | TX(Uplink):1920-1980MHz;<br>RX(Downlink):2110-2170MHz | 24.83 dBm |
| WCDMA B8 | TX(Uplink): 880-915MHz;<br>RX(Downlink):925-960MHz | 25.54dBm |
| LTE FDD B1 | TX(Uplink):1920-1980MHz;<br>RX(Downlink):2110-2170MHz | 24.20 dBm |
| LTE FDD B3 | TX(Uplink) :1710-1785MHz;<br>RX(Downlink):1805-1880MHz | 24.68 dBm |
| LTE FDD B7 | TX(Uplink) :2500-2570MHz;<br>RX(Downlink):2620-2690MHz | 23.49 dBm |
| LTE FDD B8 | TX(Uplink): 880MHz to 915 MHz<br>RX(Downlink): 925 MHz to 960 MHz | 24.61 dBm |
| LTE FDD B20 | TX(Uplink): 832MHz~862MHz;<br>RX(Downlink):791MHz~821MHz | 24.63 dBm |
| LTE FDD B28 | TX(Uplink): 703 MHz to 748MHz<br>RX(Downlink): 758 MHz to 803 MHz | 24.58 dBm |
| SA N1 | 1920-1980 MHz (TX), 2110-2170 MHz (RX) | 22.41 dBm |
| SA N 3 | 1710-1785 MHz (TX), 1805-1880 MHz (RX) | 22.34 dBm |
| SA N 8 | 880-915 MHz (TX), 925-960 MHz (RX) | 23.24 dBm |

| | | |
|---|---|---|
| SA N 20 | 832-862 MHz (TX), 791-821 MHz (RX) | 23.07dBm |
| SA N 28 | 703-748 MHz (TX), 758-803 MHz (RX) | 22.88 dBm |
| SA N 40 | 2300-2400 MHz (TX), 2300-2400 MHz (RX) | 22.94dBm |
| SA N 77 | 3700-3800 MHz (TX), 3700-3800 MHz (RX) | 25.20dBm |
| SA N 78 | 3300-3800MHz(TX), 3300-3800MHz(RX) | 25.25 dBm |
| GPS | Rx(Downlink): 1.57542GHz | -- |

Tests for SAR are conducted using standard operating positions with the device transmitting at its highest certified power level in all tested frequency bands. The maximum SAR values tested on this device when used in its normal position at the ear and when used closet othe body(at a minimum distance of 5mm/0mm) are:

| | | |
|---|---|---|
| Max SAR Value(W/kg) Limitis 2.0(W/kg) for10-g | 10-gHead | 0.150 |
| | 10-gBody | 0.605 |
| Limitis 4.0(W/kg) for10-g | 10-gMemberDAS | 2.160 |

Technical file held by: Shenzhen Doke Electronic Co., LTD

801, Building3, 7th Industrial Zone, Yulv Community, Yutang Road, Guangming District, Shenzhen, China

**Signed for and on behalf of:** Shenzhen Doke Electronic Co., LTD

**Name and Title:** Xie Ce/Manager

**Address:** 801, Building3, 7th Industrial Zone, Yulv Community, Yutang Road, Guangming District, Shenzhen, China



Signature of Authorized Person

2025-11-18