Declaration of Conformity (DoC)

We, Shenzhen Doke Electronic Co., LTD
801, Building3, 7th Industrial Zone, Yulv Community, Yutang Road, Guangming District, Shenzhen, China

Declare that the DoC is issued under our sole responsibility and belongs to the following product(s):

Product Type:	Smart Phone
Trademark:	Blackview
Model Number(s):	ROCK 5, BV9300Pro Plus
Hardware Version:	E5J7_MAIN_PCB_V1.1
Software Version:	N/A
Operating system:	Android

(Name of product, type or model, batch or serial number)

System components:

PIFA Antenna; gain: BT/Wi-Fi2.4G: 1.45dBi;

WIFI5G:1.09dBi; GSM900:-4.21dBi/DCS1800:0.17dBi

WCDMA:Band Ⅰ:0.84dBi ;Band Ⅷ:-4.58dBi;

LTE: Band 1: 0.89dBi; Band 3: 0.18dBi; Band 7:1.37dBi; Band 8: -4.24dBi; Band 20:

-5.85dBi; Band 28: -6.54dBi; GPS: PIFA Antenna; NFC: Coil Antenna

FM: Use earphone as Antenna

Adapter:
Model: QZ-03301EC00

Brand: Blackview

Input: 100-240~50/60Hz 1.2A

Output: 5.0V 3.0A 15.0W or 9.0V 3.0A 27.0W or 12.0V 2.5A 30.0W or 15.0V 2.0A 30.0W or 20.0V 1.5A 30.0W Max

PPS: 5.0V-11.0V 3.0A 33.0W Max

Manufacturer: Guangdong Quanzhi Technology

Co.,Ltd. Rechargeable Li-ion Battery:

Model: U476591PNJ; Specification: DC 3.85V, 5000mAh,19.25Wh

Manufacturer: Guangdong Quanzhi Technology Co.,Ltd

USB Cable: 110cm;



The object of the declaration described above is in conformity with the essential requirements of the relevant Union harmonization legislation: Radio Equipment Directive *RED (2014/53/EU)*.

The following *harmonized* standards and technical specifications have been applied:

HEALTH & SAFETY (Art. 3(1)(a)):

EN IEC 62368-1:2020+A11:2020
EN 50360: 2017+A1:2023;
EN 50566: 2017+A1:2023
EN IEC/IEEE 62209-1528: 2021
EN 50663: 2017; EN 62479: 2010

EMC (Art. 3(1)(b)):
EN 301 489-1 V2.2.3 (2019-11)
EN 301 489-3 V2.3.2 (2023-01)
EN 301 489-17 V3.3.1(2024-09)
EN 301 489-19 V2.2.1 (2022-09)
EN 301 489-52 V1.3.1 (2024-11)
EN 55032:2015+A11:2020
EN IEC 61000-3-2:2019+A2:2024
EN 61000-3-3:2013+A2:2021+AC:2022
EN 55035:2017+A11:2020
Radio Spectrum (Article 3.2):
EN 301 511 V12.5.1 (2017-03)
TS 151 010-1 V13.14.0 (2024-06)
EN 301 908-1 V15.2.1 (2023-01)
EN 301 908-2 V13.1.1 (2020-06)
EN 301 908-13 V13.3.1 (2024-10)
EN 300 328 V2.2.2 (2019-07)
EN 301 893 V2.1.1 (2017-05)
EN 300 440 V2.2.1 (2018-07)
EN 303 345-1 V1.1.1 (2019-06)
EN 303 345-3 V1.1.1 (2021-06)
EN 303 413 V1.2.1 (2021-04)
EN300 330 V2.1.1 (2017-02)

The submitted samples of the above equipment has been tested and found to comply with the following European Directives: RoHS Directive 2011/65/EU & (EU) 2015/863

NOTIFIEDBODY:
Name: LGAI Technological Center S.A. (APPLUS)

Address: Campus UAB. Ronda de la Font del Carme s/n08193 Bellaterra, Barcelona (Spain)

IdentificationNumber: 0370

EU-type examination certificate number: No. 0370-RED-11439

RF Specification:

Functiion	Operatiion Frequency	Max RF output power:
BLE 1M	2402MHz–2480MHz	3.95 dBm
BT(BR+EDR)	2402MHz–2480MHz	3.65 dBm
WIFI 802.11b/g/ n(HT20/40)	802.11b/g/n(20MHz): 2412~2472MHz; 802.11n(40MHz):2422~2462MHz	13.95dBm
Wi-Fi 5.2G(802.11a/n20/n40/ac20/ac40/ac80)	802.11a/ n20/ac20:5180MHz~5240MHz 802.11 n40/ac40:5190MHz~5230MHz 802.11 ac80:5210MHz	13.58 dBm
Wi-Fi 5.8G(802.11a/n20/n40/ac20/ac40/ac80)	802.11a/ n20/ac20:5745MHz~5825MHz 802.11 n40/ac40:5755MHz~5795MHz 802.11 ac80:57750MHz	11.60 dBm
GSM/GPRS/EGPRS 900	TX(Uplink):880M-915MHZ; RX(Downlink):925M-960MHZ	32.84 dBm
GSM/GPRS/EGPRS 1800	TX(Uplink):1710M-1785MHZ; RX(Downlink):1805M-1880MHZ	29.94 dBm
WCDMA B1	TX(Uplink):1920-1980MHz; RX(Downlink):2110-2170MHz	22.86 dBm
WCDMA B8	TX(Uplink): 880-915MHz; RX(Downlink):925-960MHz	23.84 dBm
LTE FDD B1	TX(Uplink):1920-1980MHz; RX(Downlink):2110-2170MHz	23.37dBm
LTE FDD B3	TX(Uplink) :1710-1785MHz; RX(Downlink):1805-1880MHz	22.65 dBm
LTE FDD B7	TX(Uplink) :2500-2570MHz; RX(Downlink):2620-2690MHz	22.56 dBm
LTE FDD B8	TX(Uplink): 880MHz to 915 MHz RX(Downlink): 925 MHz to 960 MHz	22.94 dBm
LTE FDD B20	TX(Uplink): 832MHz~862MHz; RX(Downlink):791MHz~821MHz	23.11 dBm
LTE FDD B28	TX(Uplink): 703-748 MHz (TX), RX(Downlink): 758-803 MHz	22.98dBm
FM	Rx(Downlink): 87.5MHz~108MHz	--
GPS	Rx(Downlink): 1.57542GHz	--
NFC	13.56 MHz	-40.46dBm

Tests for SAR are conducted using standard operating positions with the device transmitting at its highest certified power level in all tested frequency bands. The maximum SAR values tested on this device when used in its normal position at the ear and when used closet othe body(at a minimum distance of 0mm) are:

Max SAR Value(W/kg) Limitis 2.0(W/kg) for10-g	Head	0.785 W/kg
	Body	0.534W/kg
Max SAR Value(W/kg) Limitis 4.0(W/kg) for10-	Member DAS	0.534W/kg

Technical file held by: Shenzhen Doke Electronic Co., LTD
Address: 801, Building3, 7th Industrial Zone, Yulv Community, Yutang Road, Guangming District, Shenzhen, China

Signed for and on behalf of: Shenzhen Doke Electronic Co., LTD

Name and Title: Hong zongqing/ Manager

Address: 801, Building3, 7th Industrial Zone, Yulv Community, Yutang Road, Guangming District, Shenzhen, China

Hong zongqing
Signature of Authorized Person

2026.5.6