Declaration of Conformity (DoC)

We, Shenzhen DOKE Electronic Co., Ltd
801, Building3, 7th Industrial Zone, Yulv Community, Yutang Road, Guangming District, Shenzhen, China.

Declare that the DoC is issued under our sole responsibility and belongs to the following product(s):

Product Type:	Mobile Phone
Trademark：	Blackview / OSCAL
Model Number(s):	FORT 2, FORT 100, MARINE 3

(Name of product, type or model, batch or serial number)

System components:

PIFA Antenna: BT/Wi-Fi2.4G:1.68dBi; WIFI5.2G:1.42 dBi ; WIFI5.8G:1.42 dBi

GSM900: -1.10 dBi, DCS1800: 0.65 dBi; WCDMA Band Ⅰ: 1.0dBi ;Band Ⅷ:-1.10dBi;

LTE: Band 1: 1.0dBi; Band 3: 0.66dBi; Band 7: 1.22dBi; Band 8: -1.10dBi; Band 20: -1.12dBi; Band 28: -2.22dBi;

GPS: PIFA Antenna

Adapter:

Model: QZ-0180AEA00

Brand: Blackview / OSCAL

Input: 100-240V~50/60Hz 0.5A

Output: 9.0V 2.0A 18.0W

Manufacturer: Guangdong Quanzhi Technology Co., Ltd.

Rechargeable Li-ion Battery:

Model: LiFHPS496487PFH; Specification: DC 3.87V, 5000mAh

Manufacturer: Guangdong Fenghua New Energy Co.,Ltd.

USB Cable: 100cm;





The object of the declaration described above is in conformity with the essential requirements of the relevant Union harmonization legislation: Radio Equipment Directive *RED (2014/53/EU)*.

The following *harmonized* standards and technical specifications have been applied:

HEALTH & SAFETY (Art. 3(1)(a)):

EN 50360:2017/A1:2023 EN 50566:2017/A1:2023 EN IEC/IEEE 62209-1528:2021 EN 50663:2017 EN 62479:2010

EN 62368-1:2020+A11:2020

EMC (Art. 3(1)(b)):

ETSI EN 301 489-1 V2.2.3 (2019-11)

ETSI EN 301 489-3 V2.3.2 (2023-01)

ETSI EN 301 489-17 V3.3.1 (2024-09)

ETSI EN 301 489-19 V2.2.1 (2022-09)

ETSI EN 301 489-52 V1.3.1 (2024-11)

EN 55032:2015+A1:2020; EN 55035:2017+A11:2020

EN IEC 61000-3-2:2019/A2:2024; EN 61000-3-3:2013+A2:2021/AC:2022

Radio Spectrum (Article 3.2):

ETSI EN 301 511 V12.5.1 (2017-03);

ETSI EN 301 908-1 V15.2.1 (2023-01)

ETSI EN 301 908-2 V13.1.1 (2020-06)

ETSI EN 301 908-13 V13.3.1 (2024-10)

EN 300 328 V2.2.2 (2019-07);

EN 301 893 V2.1.1 (2017-05);

EN 300 440 V2.2.1 (2018-07);

EN 303 345-1 V1.1.1 (2019-06);

EN 303 345-3 V1.1.1 (2021-06);

EN 303 413 V1.2.1 (2021-04);

The submitted samples ofthe above equipment has been tested and found to comply with the following European Directives: RoHS Directive 2011/65/EU& (EU) 2015/863

NOTIFIEDBODY:
Name:DERYCOM CERTIFICATION SERVICES, INC.
Address:1100 FalconAvenueGlencoe,Mn55336
IdentificationNumber:3052
EU-typeexaminationcertificatenumber:JEC-36

RF Specification:

Functon	Operaton Frequency	Max RF output power:
BLE	2402MHz–2480MHz	2.56 dBm
BT(BR+EDR)	2402MHz–2480MHz	3.377 dBm
WIFI 802.11b/g/ n/ax(HT20/40)	802.11b/g/n/ax(20MHz): 2412~2472MHz; 802.11n/ax(40MHz):2422~2462MHz	13.99dBm
Wi-Fi 5.2G(802.11a/n20/ac 20)	802.11a/ n20/ac&ax 20:5180MHz~5240MHz 802.11 n40/ac&ax 40:5190MHz~5230MHz 802.11 ac&ax 80:5210MHz	12.79dBm
Wi-Fi 5.8G(802.11a/n20/n40/ac 20/ac40/ac80/ax20/ax40/ ax80)	802.11a/ n20/ac&ax 20:5745MHz~5825MHz 802.11 n40/ac&ax 40:5755MHz~5795MHz 802.11 ac&ax 80:57750MHz	10.53 dBm
GSM/GPRS/EGPRS 900	TX(Uplink):880M-915MHZ; RX(Downlink):925M-960MHZ	33.97dBm
GSM/GPRS/EGPRS 1800	TX(Uplink):1710M-1785MHZ; RX(Downlink):1805M-1880MHZ	29.98 dBm
WCDMA B1	TX(Uplink):1920-1980MHz; RX(Downlink):2110-2170MHz	23.66 dBm
WCDMA B8	TX(Uplink): 880-915MHz; RX(Downlink):925-960MHz	23.88 dBm
LTE FDD B1	TX(Uplink):1920-1980MHz; RX(Downlink):2110-2170MHz	23.45dBm
LTE FDD B3	TX(Uplink) :1710-1785MHz; RX(Downlink):1805-1880MHz	23.24 dBm
LTE FDD B7	TX(Uplink) :2500-2570MHz; RX(Downlink):2620-2690MHz	24.71 dBm
LTE FDD B8	TX(Uplink): 880MHz to 915 MHz RX(Downlink): 925 MHz to 960 MHz	23.92 dBm
LTE FDD B20	TX(Uplink): 832MHz~862MHz; RX(Downlink):791MHz~821MHz	24.36 dBm
LTE FDD B28	TX(Uplink): 703 MHz to 748MHz RX(Downlink): 758 MHz to 803 MHz	23.66 dBm
FM	Rx(Downlink): 87.5MHz~108MHz	--
GPS	Rx(Downlink): 1.57542GHz	--

Tests for SAR are conducted using standard operating positions with the device transmitting at its highest certified power level in all tested frequency bands. The maximum SAR values tested on this device when used in its normal position at the ear and when used closet othe body(at a minimum distance of 5mm/0mm) are:

Max SAR Value(W/kg) Limitis 2.0(W/kg) for10-g	10-gHead	1.689
	10-gBody	1.455
Limitis 4.0(W/kg) for10-g	10-gMemberDAS	2.634

Technical file held by: Shenzhen DOKE ElectronicCo.,Ltd
801, Building3, 7th Industrial Zone, YulvCommunity, YutangRoad, GuangmingDistrict,Shenzhen, China.

Signed for and on behalf of: Shenzhen DOKE ElectronicCo.,Ltd

Name and Title: Lynne Chen/Manager

Address: 801, Building3, 7th Industrial Zone, YulvCommunity, YutangRoad, GuangmingDistrict,Shenzhen, China.

Lynne Chen

Signature of Authorized Person

2025-10-23